

LOW POWER 50 OHM SMA FIXED ATTENUATORS

Model	Frequency Range	Attenuation Values	Attenuation Accuracy	VSWR Maximum	Input Power
351-015-XXX*	DC - 1 GHz	1 - 40 dB in 1 dB increments	+/-0.3 dB, 1 - 20 dB +/-0.5 dB, 21 - 40 dB	1.20:1	1 Watt Average
351-024-XXX*	DC - 2.2 GHz	1 - 40 dB in 1 dB increments	+/-0.5 dB, 1 - 20 dB +/-0.75 dB, 21 - 40 dB	1.20:1, DC - 1 GHz 1.40:1, 1 - 2.2 GHz	1 Watt Average
351-129-XXX*	DC - 2.5 GHz	1 - 40 dB in 1 dB increments	+/-0.5 dB, 1 - 10 dB +/-0.75 dB, 11 - 20 dB +/-1.0dB, 21 - 40 dB	1.40:1	1 Watt Average
351-057-XXX*	DC - 3 GHz	1 - 40 dB in 1 dB increments	+/-0.5 dB, 1 - 10 dB +/-0.75 dB, 11 - 20 dB +/-1.0 dB, 21 - 40 dB	1.40:1	1 Watt Average
351-013-XXX*	DC - 18 GHz	1 - 30 and 40 dB in 1 dB	+/-0.3 dB, 1 - 6 dB +/-0.5 dB, 7 - 20 dB +/-0.75 dB, 21 - 30 dB +/-1.0 dB, 40 dB	1.15:1, DC - 4 GHz 1.20:1, 4 - 8 GHz 1.25:1, 8 - 12.4 GHz 1.35:1, 12.4 - 18 GHz	2 Watts Average
351-052-XXX*	DC - 26.5 GHz	1 - 20, 30 and 40 dB	+/-0.8 dB, 1 - 20 dB +/-1.5 dB, 30 & 40 dB	1.35:1, DC - 18 GHz 1.50:1, 18 - 26.5 GHz	2 Watts Average
351-260-XXX*	DC - 6 GHz	1 - 12, 15, 20 and 30 dB	+/-0.75 dB, 1 - 12 dB +/-1.0 dB, 15 & 20 dB +/-1.25 dB, 30 dB	1.25:1	5 Watts Average
351-259-XXX*	DC - 18 GHz	1 - 12, 15, 20 and 30 dB	+/-0.75 dB, 1 - 12 dB +/- 1.0 dB, 15 & 20 dB +/-1.25 dB, 30 dB	1.35:1	5 Watts Average

MEDIUM POWER 50 OHM SMA FIXED ATTENUATORS

Model	Frequency Range	Attenuation Values	Attenuation Accuracy	VSWR Maximum	Input Power
351-234-XXX*	DC - 4 GHz	3, 6, 10, 20 and 30 dB	+/-0.3 dB, 3 & 6 dB +/-0.5 dB, 10 dB +/-0.75 dB, 20 & 30 dB	1.20:1	10 Watts Average
351-241-XXX*	DC - 18 GHz	3, 6, 10, 20 and 30 dB	+/-0.75 dB, 3, 6 & 10 dB +/-1.0 dB, 20 dB +/-1.25 dB, 30 dB	1.45:1	10 Watts Average
351-249-XXX*	DC - 3 GHz	1 - 30 dB in 1 dB increments	+/-0.5 dB, 1 - 10 dB +/-1.0 dB, 11 - 30 dB	1.20:1, DC - 1 GHz 1.40:1, 1 - 3 GHz	30 Watts Average

HIGH POWER 50 OHM SMA FIXED ATTENUATORS

Model	Frequency Range	Attenuation Values	Attenuation Accuracy	VSWR Maximum	Input Power
351-248-XXX*	DC - 3 GHz	1 - 30 dB and 40 dB	+/-1.0 dB, 1 - 10 dB +/-1.5 dB, 11 - 30 & 40 dB	1.20:1, DC - 1 GHz 1.40:1, 1 - 3 GHz	50 Watts Average
351-255-XXX*	DC - 3 GHz	3, 6, 10, 20, 30 and 40 dB	+/-0.75 dB, 3, 6 & 10 dB +/-1.0 dB, 20 & 30 dB +/-1.5 dB, 40 dB	1.20:1, DC - 1 GHz 1.40:1, 1 - 3 GHz	100 Watts Average

CONDUCTION COOLED 50 OHM SMA FIXED ATTENUATORS

Model	Frequency Range	Attenuation Values	Attenuation Accuracy	VSWR Maximum	Input Power
351-251-XXX*	DC - 1 GHz	1 - 40 dB in 1 dB increments	+/-0.5 dB, 1-10 dB +/-1.0 dB, 11-20 dB +/-1.5 dB, 21-40 dB	1.35:1	10 Watts Average
351-250-XXX*	DC - 1 GHz	1 - 40 dB in 1 dB increments	+/-0.5 dB, 1-10 dB +/-1.0 dB, 11-20 dB +/-1.5 dB, 21-40 dB	1.35:1	100 Watts Average

*Insert desired attenuation value (example: 3 dB = 003).

Complete specifications and outline drawings are available on our web site or consult the factory.



2900 Graham Road, Suite B Franklin, IN 46131 USA
tel: 317.346.6101 fax: 317.346.6995

LOW POWER 50 OHM N FIXED ATTENUATORS

Model	Frequency Range	Attenuation Values	Attenuation Accuracy	VSWR Maximum	Input Power
352-011-XXX*	DC - 1 GHz	1 - 20 dB and 30 dB	+/-0.3 dB, 1 - 10 dB +/-0.5 dB, 11 - 20 dB +/-1.0 dB, 30 dB	1.30:1, 1 - 20 dB 1.20:1, 30 dB	1 Watt Average
352-016-XXX*	DC - 2.2 GHz	1 - 40 dB in 1 dB increments	+/-0.5 dB, 1 - 20 dB +/-0.75 dB, 21 - 40 dB	1.30:1, DC - 1 GHz 1.40:1, 1 - 2.2 GHz	1 Watt Average
352-129-XXX*	DC - 2.5 GHz	1 - 40 dB in 1 dB increments	+/-0.5 dB, 1 - 10 dB +/-0.75 dB, 11 - 20 dB +/-1.0 dB, 21 - 40 dB	1.40:1	1 Watt Average
352-057-XXX*	DC - 3 GHz	1 - 40 dB in 1 dB increments	+/-0.5 dB, 1 - 10 dB +/-0.75 dB, 11 - 20 dB +/-1.0 dB, 21 - 40 dB	1.40:1	1 Watt Average
352-276-XXX*	DC - 3 GHz	40 - 80 dB in 1 dB increments	+/-1.75 dB, 40 - 80 dB	1.40:1	1 Watt Average
352-118-XXX*	DC - 2 GHz	1 - 40 dB in 1 dB increments	+/-0.5 dB, 1 - 20 dB +/-1.0 dB, 21 - 40 dB	1.40:1	2 Watts Average
352-126-XXX*	DC - 2.2 GHz	1 - 40 dB in 1 dB increments	+/-0.5 dB, 1 - 20 dB +/-1.0 dB, 21 - 40 dB	1.40:1	2 Watts Average
352-035-XXX*	DC - 4 GHz	1 - 3, 6, 10, 16, 19, 20 & 30 dB	+/-0.3 dB, 1 - 19 dB +/-0.5 dB, 20 & 30 dB	1.20:1	2 Watts Average
352-103-XXX*	DC - 6 GHz	1 - 30 and 40 dB	+/-0.5 dB, 1 - 20 dB +/-0.75 dB, 21 - 30 dB +/-1.5 dB, 40 dB	1.35:1	2 Watts Average
352-125-XXX*	DC - 12.4 GHz	1 - 40 dB and 50 dB	+/-0.3 dB, 1 - 6 dB +/-0.5 dB, 7 - 20 dB +/-0.75 dB, 21 - 30 dB +/-1.5 dB, 31 - 40 & 50 dB	1.15:1, DC - 4 GHz 1.20:1, 4 - 8 GHz 1.25:1, 8 - 12.4 GHz	2 Watts Average
352-019-XXX*	DC - 18 GHz	1 - 30 dB in 1 dB increments	+/-0.3 dB, 1 - 6 dB +/-0.5 dB, 7 - 20 dB +/-0.75 dB, 21 - 30 dB	1.15:1, DC - 4 GHz 1.20:1, 4 - 8 GHz 1.35:1, 8 - 18 GHz	2 Watts Average
352-230-XXX*	DC - 4 GHz	1 - 12, 15, 20 and 30 dB	+/-0.3 dB, 1 - 9 dB +/-0.5 dB, 10-12 & 15 dB +/-0.75 dB, 20 & 30 dB	1.20:1	5 Watts Average
352-232-XXX*	DC - 18 GHz	1 - 12, 15, 20 and 30 dB	+/-0.5 dB, 1 - 9 dB +/-0.75 dB, 10-12 & 15 dB +/-1.0 dB, 20 & 30 dB	1.35:1	5 Watts Average

MEDIUM POWER 50 OHM N FIXED ATTENUATORS

Model	Frequency Range	Attenuation Values	Attenuation Accuracy	VSWR Maximum	Input Power
352-231-XXX*	DC - 4 GHz	3, 6, 10, 20, 30 and 40 dB	+/-0.5 dB, 3 & 6 dB +/-0.75 dB, 10 dB +/-1.0 dB, 20, 30 & 40 dB	1.20:1	10 Watts Average
352-233-XXX*	DC - 18 GHz	3, 6, 10, 20 and 30 dB	+/-0.5 dB, 3 & 6 dB +/-0.75 dB, 10 dB +/-1.0 dB, 20 & 30 dB	1.45:1	10 Watts Average
352-271-XXX*	DC - 6 GHz	3, 6, 10, 20, 30 and 40 dB	+/-0.3 dB, 3 & 6 dB +/-0.5 dB, 10 & 20 dB +/-0.75 dB, 30 dB +/-1.0 dB, 40 dB	1.20:1	25 Watts Average
352-178-XXX*	DC - 2 GHz	1 - 30 dB in 1 dB increments	+/-0.5 dB, 1 - 10 dB +/-1.0 dB, 11 - 30 dB	1.20:1, DC - 1 GHz 1.35:1, 1 - 2 GHz	30 Watts Average
352-249-XXX*	DC - 3 GHz	1 - 30 dB in 1 dB increments	+/-0.5 dB, 1 - 10 dB +/-1.0 dB, 11 - 30 dB	1.20:1, DC - 1 GHz 1.40:1, 1 - 3 GHz	30 Watts Average

*Insert desired attenuation value (example: 3 dB = 003).

Male to Female connectors are the standard configuration, other configurations are available.
Complete specifications and outline drawings are available on our web site or consult the factory.



Visit our website for the most
up-to-date product listings!
www.broadwavetech.com



HIGH POWER 50 OHM N FIXED ATTENUATORS

Model	Frequency Range	Attenuation Values	Attenuation Accuracy	VSWR Maximum	Input Power
352-135-XXX*	DC - 2.2 GHz	1 - 30 dB in 1 dB increments	+/-1.0 dB, 1 - 10 dB +/-1.5 dB, 11 - 30 dB	1.20:1, DC - 1 GHz 1.35:1, 1 - 2.2 GHz	50 Watts Average
352-248-XXX*	DC - 3 GHz	1 - 30 dB and 40 dB	+/-1.0 dB, 1 - 10 dB +/-1.5 dB, 11 - 30 & 40 dB	1.20:1, DC - 1 GHz 1.40:1, 1 - 3 GHz	50 Watts Average
352-094-XXX*	DC - 6 GHz	3, 6, 10, 20, 30 and 40 dB	+/-0.75 dB, 3 - 30 dB +/-1.0 dB, 40 dB	1.25:1	50 Watts Average
352-171-XXX*	DC - 12.4 GHz	3, 6, 10, 20, 30 and 40 dB	+/-0.75 dB, 3 & 6dB +/-1.0 dB, 10 & 20 dB +/-1.25 dB, 30 dB +/-1.5 dB, 40 dB	1.45:1	50 Watts Average
352-050-XXX*	DC - 18 GHz	3, 6, 10, 20, 30 and 40 dB	+/-0.75 dB, 3 & 6 dB +/-1.0 dB, 10 & 20 dB +/-1.25 dB, 30 dB +/-1.5 dB, 40 dB	1.45:1	50 Watts Average
352-136-XXX*	DC - 2.2 GHz	1 - 30 and 40 dB	+/-0.5 dB, 1 - 10 dB +/-1.0 dB, 11 - 30 dB +/-1.5 dB, 40 dB	1.20:1, DC - 1 GHz 1.40:1, 1 - 2.2 GHz	100 Watts Average
352-270-XXX*	DC - 2.5GHz	3, 6, 10, 20, 30 and 40 dB	+/-0.5 dB, 3, 6 & 10 dB +/-1.0 dB, 20 & 30 dB +/-1.5 dB, 40 dB	1.20:1, DC - 1 GHz 1.40:1, 1 - 2.5 GHz	100 Watts Average
352-255-XXX*	DC - 3 GHz	3, 6, 10, 20, 30 and 40 dB	+/-0.75 dB, 3, 6 & 10 dB +/-1.0 dB, 20 & 30 dB +/-1.5 dB, 40 dB	1.20:1, DC - 1 GHz 1.40:1, 1 - 3 GHz	100 Watts Average
352-137-XXX*	DC - 2.2 GHz	1 - 30 dB in 1 dB increments	+/-0.5 dB, 1 - 10 dB +/-1.0 dB, 11 - 30 dB	1.20:1, DC - 1 GHz 1.35:1, 1 - 2.2 GHz	150 Watts Average
352-017-XXX*	DC - 3 GHz	1, 2, 3, 6, 10, 20 and 30 dB	Consult the Factory	1.25:1	150 Watts Average
352-138-XXX*	DC - 2.2 GHz	1 - 30 dB in 1 dB increments	+/-0.5 dB, 1 - 10 dB +/-1.0 dB, 11 - 30 dB	1.20:1, DC - 1 GHz 1.35:1, 1 - 2.2 GHz	200 Watts Average
352-177-XXX*	DC - 2.5 GHz	1 - 30 dB in 1 dB increments	+/-0.5 dB, 1 - 10 dB +/-1.0 dB, 11 - 30 dB	1.20:1, DC - 1 GHz 1.40:1, 1 - 2.5 GHz	200 Watts Average
352-023-XXX*	DC - 2.4 GHz	1, 3, 6, 10, 20, 30 and 40 dB	Consult the Factory	1.25:1	300 Watts Average
352-228-XXX*	DC - 3 GHz	1, 3, 6, 10, 20, 30 and 40 dB	Consult the Factory	1.30:1	300 Watts Average
352-047-XXX*	DC - 2.5 GHz	3, 6, 10, 20 and 30 dB	Consult the Factory	1.25:1	500 Watts Average
352-045-XXX*	DC - 2.4 GHz	3, 6, 10, 20 and 30 dB	Consult the Factory	1.25:1	1,000 Watts Average

CONDUCTION COOLED 50 OHM N FIXED ATTENUATORS

Model	Frequency Range	Attenuation Values	Attenuation Accuracy	VSWR Maximum	Input Power
352-226-XXX*	DC - 1 GHz	1 - 40 dB in 1 dB increments	+/-0.5 dB, 1-10 dB +/-1.0 dB, 11-20 dB +/-1.5 dB, 21-40 dB	1.35:1	25 Watts Average
352-262-XXX*	DC - 3 GHz	1 - 30 and 40 dB	+/-0.5 dB, 1-10 dB +/-1.0 dB, 11-20 dB +/-1.5 dB, 30 & 40 dB	1.20:1, DC - 1 GHz 1.40:1, 1 - 3 GHz	50 Watts Average
352-227-XXX*	DC - 1 GHz	1 - 40 dB in 1 dB increments	+/-0.5 dB, 1-10 dB +/-1.0 dB, 11-20 dB +/-1.5 dB, 21-40 dB	1.35:1	100 Watts Average
352-263-XXX*	DC - 2.5 GHz	1 - 30 and 40 dB	+/-0.5 dB, 1-10 dB +/-1.0 dB, 11-20 dB +/-1.5 dB, 30 & 40 dB	1.35:1, DC - 1 GHz 1.40:1, 1 - 2.5 GHz	100 Watts Average

*Insert desired attenuation value (example: 3 dB = 003).

Some high power units are uni-directional.

Male to Female connectors are the standard configuration, other configurations are available.
Complete specifications and outline drawings are available on our web site or consult the factory.



2900 Graham Road, Suite B Franklin, IN 46131 USA
tel: 317.346.6101 fax: 317.346.6995



LOW POWER 50 OHM TNC FIXED ATTENUATORS

Model	Frequency Range	Attenuation Values	Attenuation Accuracy	VSWR Maximum	Input Power
353-012-XXX*	DC - 1 GHz	1 - 20 dB in 1 dB increments	+/-0.5 dB, 1 - 20 dB	1.20:1	1 Watt Average
353-095-XXX*	DC - 2 GHz	1 - 20 and 30 dB	+/-0.3 dB, 1 - 6 dB +/-0.4 dB, 7 - 10 dB +/-0.8 dB, 11 - 20 dB +/-1.0 dB, 30 dB	1.25:1	1 Watt Average
353-022-XXX*	DC - 2.2 GHz	1 - 40 dB in 1 dB increments	+/-0.5 dB, 1 - 20 dB +/-0.75 dB, 21 - 20 dB	1.30:1, DC - 1 GHz 1.40:1, 1 - 2.2 GHz	1 Watt Average
353-129-XXX*	DC - 2.5 GHz	1 - 40 dB in 1 dB increments	+/-0.5 dB, 1 - 10 dB +/-0.75 dB, 11 - 20 dB +/-1.0 dB, 21 - 40 dB	1.40:1	1 Watt Average
353-057-XXX*	DC - 3 GHz	1 - 40 dB in 1 dB increments	+/-0.5 dB, 1 - 10 dB +/-0.75 dB, 11 - 20 dB +/-1.0 dB, 21 - 40 dB	1.40:1	1 Watt Average
353-124-XXX*	DC - 2 GHz	1 - 20 dB in 1 dB increments	+/-0.3 dB, 1 - 3 dB +/-0.4 dB, 4 - 15 dB +/-0.5 dB, 16 - 20 dB	1.30:1	2 Watts Average

MEDIUM POWER 50 OHM TNC FIXED ATTENUATORS

Model	Frequency Range	Attenuation Values	Attenuation Accuracy	VSWR Maximum	Input Power
353-249-XXX*	DC - 3 GHz	1 - 30 dB in 1 dB increments	+/-0.5 dB, 1 - 10 dB +/-1.0 dB, 11 - 30 dB	1.20:1, DC - 1 GHz 1.40:1, 1 - 3 GHz	30 Watts Average

HIGH POWER 50 OHM TNC FIXED ATTENUATORS

Model	Frequency Range	Attenuation Values	Attenuation Accuracy	VSWR Maximum	Input Power
353-248-XXX*	DC - 3 GHz	1 - 30 and 40 dB	+/-1.0 dB, 1 - 10 dB +/-1.5 dB, 11 - 30 & 40 dB	1.20:1, DC - 1 GHz 1.40:1, 1 - 3 GHz	50 Watts Average
353-136-XXX*	DC - 2.2 GHz	1 - 30 and 40 dB	+/-0.5 dB, 1 - 10 dB +/-1.0 dB, 11 - 30 dB +/-1.5 dB, 40 dB	1.20:1, DC - 1 GHz 1.40:1, 1 - 2.2 GHz	100 Watts Average

LOW POWER 50 OHM BNC FIXED ATTENUATORS

Model	Frequency Range	Attenuation Values	Attenuation Accuracy	VSWR Maximum	Input Power
354-012-XXX*	DC - 1 GHz	1 - 20 dB in 1 dB increments	+/-0.5 dB, 1 - 20 dB	1.20:1	1 Watt Average
354-095-XXX*	DC - 2 GHz	1 - 40 dB in 1 dB increments	+/-0.5 dB, 1 - 20 dB +/-0.8 dB, 21 - 40 dB	1.30:1, DC - 1 GHz 1.40:1, 1 - 2 GHz	1 Watt Average
354-014-XXX*	DC - 2.2 GHz	1 - 40 dB in 1 dB increments	+/-0.5 dB, 1 - 20 dB +/-0.75 dB, 21 - 40 dB	1.30:1, DC - 1 GHz 1.40:1, 1 - 2.2 GHz	1 Watt Average

MEDIUM POWER 50 OHM BNC FIXED ATTENUATORS

Model	Frequency Range	Attenuation Values	Attenuation Accuracy	VSWR Maximum	Input Power
354-249-XXX*	DC - 3 GHz	1 - 30 dB in 1 dB increments	+/-0.5 dB, 1 - 10 dB +/-1.0 dB, 11 - 30 dB	1.20:1, DC - 1 GHz 1.40:1, 1 - 3 GHz	30 Watts Average

HIGH POWER 50 OHM BNC FIXED ATTENUATORS

Model	Frequency Range	Attenuation Values	Attenuation Accuracy	VSWR Maximum	Input Power
354-248-XXX*	DC - 2.2 GHz	1 - 30 and 40 dB	+/-1.0 dB, 1 - 10 dB +/-1.5 dB, 11 - 30 & 40 dB	1.20:1, DC - 1 GHz 1.40:1, 1 - 3 GHz	50 Watts Average
354-136-XXX*	DC - 2.2 GHz	1 - 30 and 40 dB	+/-0.5 dB, 1 - 10 dB +/-1.0 dB, 11 - 30 dB +/-1.5 dB, 40 dB	1.20:1, DC - 1 GHz 1.40:1, 1 - 2.2 GHz	100 Watts Average

*Insert desired attenuation value (example: 3 dB = 003).

Male to Female connectors are the standard configuration, other configurations are available.
Complete specifications and outline drawings are available on our web site or consult the factory.



HIGH POWER 50 OHM 7/16 FIXED ATTENUATORS

Model	Frequency Range	Attenuation Values	Attenuation Accuracy	VSWR Maximum	Input Power
355-255-XXX*	DC - 3 GHz	1 - 30 & 40 dB	+/-0.5 dB, 1 - 10 dB +/-1.0 dB, 11 - 30 dB +/-1.5 dB, 40 dB	1.20:1, DC - 1 GHz 1.40:1, 1 - 3 GHz	100 Watts Average

LOW POWER 50 OHM 2.9 mm FIXED ATTENUATORS

Model	Frequency Range	Attenuation Values	Attenuation Accuracy	VSWR Maximum	Input Power
357-021-XXX*	DC - 40 GHz	1 - 20 dB in 1 dB increments	+/-0.6 dB, 1 - 15 dB +/-1.0 dB, 16 - 20 dB	1.40:1	0.5 Watts Average

LOW POWER 50 OHM SMA MALE TO N FEMALE FIXED ATTENUATORS

Model	Frequency Range	Attenuation Values	Attenuation Accuracy	VSWR Maximum	Input Power
359-169-XXX*	DC - 2.2 GHz	1 - 40 dB in 1 dB increments	+/-0.5 dB, 1 - 20 dB +/-0.75 dB, 21 - 40 dB	1.30:1, DC - 1 GHz 1.40:1, 1 - 2.2 GHz	1 Watt Average

LOW POWER 75 OHM N FIXED ATTENUATORS

Model	Frequency Range	Attenuation Values	Attenuation Accuracy	VSWR Maximum	Input Power
372-049-XXX*	DC - 1 GHz	1 - 20 dB in 1 dB increments	+/-0.3 dB, DC - 0.5 GHz +/-0.6 dB, 0.5 - 1 GHz	1.40:1	1 Watt Average
372-182-XXX*	DC - 3 GHz	1 - 20 dB in 1 dB increments	+/-0.5 dB, 1 - 10 dB +/-1.0 dB, 11 - 20 dB	1.35:1, DC - 1 GHz 1.50:1, 1 - 3 GHz	2 Watts Average

LOW POWER 75 OHM TNC FIXED ATTENUATORS

Model	Frequency Range	Attenuation Values	Attenuation Accuracy	VSWR Maximum	Input Power
373-049-XXX*	DC - 1 GHz	1 - 20 dB in 1 dB increments	+/-0.3 dB, DC - 0.5 GHz +/-0.6 dB, 0.5 - 1 GHz	1.40:1	1 Watt Average

LOW POWER 75 OHM BNC FIXED ATTENUATORS

Model	Frequency Range	Attenuation Values	Attenuation Accuracy	VSWR Maximum	Input Power
374-095-XXX*	DC - 0.5 GHz	1 - 20 dB in 1 dB increments	+/-0.3 dB, DC - 0.1 GHz +/-0.5 dB, 0.1 - 0.5 GHz	1.30:1	1 Watt Average
374-049-XXX*	DC - 1 GHz	1 - 20 dB in 1 dB increments	+/-0.75 dB	1.40:1	1 Watt Average
374-120-XXX*	DC - 2 GHz	1 - 40 dB in 1 dB increments	+/-0.75 dB, 1 - 20 dB +/-1.0 dB, 21 - 40 dB	1.50:1	1 Watt Average

LOW POWER 75 OHM F FIXED ATTENUATORS

Model	Frequency Range	Attenuation Values	Attenuation Accuracy	VSWR Maximum	Input Power
379-143-XXX*	DC - 1 GHz	1 - 20 dB in 1 dB increments	+/-0.5 dB	1.50:1	1 Watt Average
379-225-XXX*	DC - 2 GHz	1 - 20 dB in 1 dB increments	+/-0.5 dB	1.50:1	1 Watt Average
379-256-XXX*	DC - 3 GHz	1 - 20 dB in 1 dB increments	+/-0.5 dB	1.50:1	1 Watt Average

*Insert desired attenuation value (example: 3 dB = 003).

Male to Female connectors are the standard configuration, other configurations are available.
Complete specifications and outline drawings are available on our web site or consult the factory.



2900 Graham Road, Suite B Franklin, IN 46131 USA
tel: 317.346.6101 fax: 317.346.6995