

B R O A D W A V E T E C H N O L O G I E S I N C .

MODEL 151 - 085 - XXX\*

POWER DIVIDER

**Frequency Range:** 800 - 2700 MHz

**Impedance:** 50 Ohms nominal

**Configurations:** 2 way ( - 002 )  
 \* - Insert desired configuration 3 way ( - 003 ) 800 - 2200 MHz only  
 4 way ( - 004 )

**Isolation:** 25 dB typical  
 20 dB minimum

**Insertion Loss:** 0.5 dB nominal @ 2700 MHz ( - 002 )  
 ( above theoretical split ) 0.6 dB nominal @ 2200 MHz ( - 003 )  
 1.0 dB nominal @ 2700 MHz ( - 004 )

**Amplitude Tracking:** ± 0.3 dB maximum ( - 002, - 004 )  
 ± 0.5 dB maximum ( - 003 )

**VSWR:** 1.40:1 maximum ( - 002, - 004 )  
 1.50:1 maximum ( - 003 )

**Power Input:** 5 Watts average @ 25°C

**RF Connectors:** SMA Female

**Operating Temperature Range:** - 55°C to +85°C

**Outline Drawing:** MED - 0074 ( - 002 )  
 MED - 0264 ( - 003 )  
 MED - 0087 ( - 004 )

ECF #	Date	Rev.
Issue	7/7/04	0

Approved By: \_\_\_\_\_