

B R O A D W A V E T E C H N O L O G I E S I N C .

---

MODEL 152 - 037 - XXX\*

POWER DIVIDER

---

**Frequency Range:** 500 - 1000 MHz

**Impedance:** 50 Ohms nominal

**Configurations:** 2 way ( - 002 )  
\* - Insert desired configuration 3 way ( - 003 )  
4 way ( - 004 )  
8 way ( - 008 )

**Isolation:** 25 dB typical  
20 dB minimum

**Insertion Loss:** 0.4 dB maximum ( - 002 )  
( above theoretical split ) 0.6 dB maximum ( - 003 )  
0.7 dB maximum ( - 004 )  
1.0 dB maximum ( - 008 )

**Amplitude Tracking:** ± 0.3 dB maximum ( - 002, - 003, - 004 )  
± 0.5 dB maximum ( - 008 )

**Phase Tracking:** ± 5° maximum

**VSWR:** 1.40:1 maximum ( - 002, - 003, - 004 )  
1.50:1 maximum ( - 008 )

**Power Input:** 5 Watts average @ 25°C

**RF Connectors:** N Female

**Operating Temperature Range:** - 55°C to +85°C

**Outline Drawing:** MED - 0077 ( - 002 )  
MED - 0317 ( - 003 )  
MED - 0086 ( - 004 )  
MED - 0184 ( - 008 )

ECF #	Date	Rev.
Issue	11/01/02	0
0159	6/24/03	A
0563	1/31/08	B

Approved By: \_\_\_\_\_